

How to Install Tomcat 9 on CentOS 8

Apache Tomcat is an open-source implementation of the Java Servlet, JavaServer Pages, Java Expression Language, and Java WebSocket technologies. It is one of the most widely adopted applications and web servers in the world today. Tomcat is simple to use and has a robust ecosystem of add-ons.



Installation Tutorial

This tutorial explains how to install Tomcat 9.0 on CentOS 8.

Installing Java

Tomcat 9 requires Java SE 8 or later. We will install OpenJDK 11, the open-source implementation of the Java Platform.


Run the following command as root or user with sudo privileges to install Java:

```
# dnf install java-11-openjdk-devel
```

Once the installation is complete, verify it by checking the Java version:

```
# java -version
```

The output should look something like this:



```
openjdk version "11.0.5" 2019-10-15 LTS
OpenJDK Runtime Environment 18.9 (build 11.0.5+10-LTS)
OpenJDK 64-Bit Server VM 18.9 (build 11.0.5+10-LTS, mixed mode, sharing)
```

Creating a System User

Running Tomcat under the root user is a security risk. We'll create a new system user and group with home directory /opt/tomcat that will run the Tomcat service. To do so, enter the following command:

```
# useradd -m -U -d /opt/tomcat -s /bin/false tomcat
```

Downloading Tomcat

Tomcat binary distribution is available for download from the Tomcat downloads page.

At the time of writing, the latest Tomcat version is 9.0.30. Before continuing with the next step, check the Tomcat 9 download page to see if a newer version is available.

Download the Tomcat zip file with wget to the /tmp directory:

```
# VERSION=9.0.30
# wget
https://www-eu.apache.org/dist/tomcat/tomcat-9/v${VERSION}/bin/apache-tomcat-
-${VERSION}.tar.gz -P /tmp
```

Once the download is complete, extract the tar file to the /opt/tomcat directory:

```
# tar -xf /tmp/apache-tomcat-${VERSION}.tar.gz -C /opt/tomcat/
```

Tomcat is updated on a regular basis. To have more control over versions and updates, we'll create a symbolic link called latest, that points to the Tomcat installation directory:

```
# ln -s /opt/tomcat/apache-tomcat-${VERSION} /opt/tomcat/latest
```

The system user that was previously created, must have access to the tomcat installation directory. Change the directory ownership to user and group tomcat:

```
# chown -R tomcat: /opt/tomcat
```

Make the shell scripts inside the bin directory executable:

```
# sh -c 'chmod +x /opt/tomcat/latest/bin/*.sh'
```

These scripts are later used to start and stop Tomcat from the systemd unit file.

Creating a Systemd Unit File

Instead of manually starting and stopping the Tomcat server, we'll set it to run as a service. Open your text editor and create a `tomcat.service` unit file in the `/etc/systemd/system/` directory:

```
# vim /etc/systemd/system/tomcat.service
```

Paste the following content:

```
[Unit]
Description=Tomcat 9 servlet container
After=network.target

[Service]
Type=forking

User=tomcat
Group=tomcat

Environment="JAVA_HOME=/usr/lib/jvm/jre"
Environment="JAVA_OPTS=-Djava.security.egd=file:///dev/urandom"

Environment="CATALINA_BASE=/opt/tomcat/latest"
Environment="CATALINA_HOME=/opt/tomcat/latest"
Environment="CATALINA_PID=/opt/tomcat/latest/temp/tomcat.pid"
Environment="CATALINA_OPTS=-Xms512M -Xmx1024M -server -XX:+UseParallelGC"

ExecStart=/opt/tomcat/latest/bin/startup.sh
ExecStop=/opt/tomcat/latest/bin/shutdown.sh

[Install]
WantedBy=multi-user.target
```

Save and close the file.

Notify systemd that a new service file exists, by typing:

```
# systemctl daemon-reload
```

Enable and start the Tomcat service:

```
# systemctl enable --now tomcat
```

Check the service status; the output should show that the Tomcat server is enabled and running:

```
# systemctl status tomcat
```

```
● tomcat.service - Tomcat 9 servlet container
   Loaded: loaded (/etc/systemd/system/tomcat.service; enabled; vendor
  preset: disabled)
   Active: active (running) since Wed 2020-01-15 20:38:07 UTC; 30s ago
     Process: 3957 ExecStart=/opt/tomcat/latest/bin/startup.sh (code=exited,
  status=0/SUCCESS)
   ...
```

Configuring Firewall

If your server is protected by a firewall and you want to access the tomcat interface from the outside of the local network, you need to open port 8080.

Use the following commands to open the necessary port:

```
# firewall-cmd --permanent --zone=public --add-port=8080/tcp
sudo firewall-cmd --reload
```

Typically, when running Tomcat in a production environment, you should use a load balancer or reverse proxy. It's a best practice to allow access to port 8080 only to your internal network.

Additional: Configuring Tomcat Web Management Interface

At this point, you should be able to access Tomcat with a web browser on port 8080. The web management interface is not accessible because we have not created a user yet.

Tomcat users and roles are defined in the `tomcat-users.xml` file.

If you open the file, you will notice that it is filled with comments and examples describing how to configure the file.

```
# vim /opt/tomcat/latest/conf/tomcat-users.xml
```

Tomcat users are defined the user in the `tomcat-users.xml` file. To create a new user that can access the tomcat web interface (manager-gui and admin-gui), edit file as shown below. Make sure you change the username and password to something more secure:

```
<tomcat-users>
<!--
  Comments
-->
  <role rolename="admin-gui"/>
  <role rolename="manager-gui"/>
  <user username="admin" password="admin_password" roles="admin-
  gui,manager-gui"/>
```

```
</tomcat-users>
```

By default Tomcat web management interface is configured to allow access only from the localhost.

If you need to access the web interface from anywhere open the following files and comment or remove the lines highlighted in yellow:

```
# vim /opt/tomcat/latest/webapps/manager/META-INF/context.xml
```

```
<Context antiResourceLocking="false" privileged="true" >
<!--
  <Valve className="org.apache.catalina.valves.RemoteAddrValve"
    allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1" />
-->
</Context>
```

```
# vim /opt/tomcat/latest/webapps/host-manager/META-INF/context.xml
```

```
<sxh xml>
<Context antiResourceLocking="false" privileged="true" >
<!--
  <Valve className="org.apache.catalina.valves.RemoteAddrValve"
    allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1" />
-->
</Context>
</sxh>
```

Please note, allowing access from anywhere is not recommended because it is a security risk.

If you want to access the web interface only from a specific IP, instead of commenting the blocks add your public IP to the list.

Let's say your public IP is '41.41.41.41' and you want to allow access only from that IP:

```
<code># vim /opt/tomcat/latest/webapps/manager/META-INF/context.xml
```

```
<Context antiResourceLocking="false" privileged="true" >
  <Valve className="org.apache.catalina.valves.RemoteAddrValve"
    allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1|41.41.41.41" />
</Context>
```

```
# vim /opt/tomcat/latest/webapps/host-manager/META-INF/context.xml
```

```
<Context antiResourceLocking="false" privileged="true" >
  <Valve className="org.apache.catalina.valves.RemoteAddrValve"
    allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1|41.41.41.41" />
</Context>
```

The list of allowed IP addresses is a list separated with vertical bar |. You can add single IP addresses or use a regular expressions.

Once done, restart the Tomcat service for changes to take effect:

```
# systemctl restart tomcat
```

Testing Management Interface Installation

Open your browser and type: http://<your_domain_or_IP_address>:8080

Upon successful installation, a screen similar to the following should appear:

Apache Tomcat/9.0.13



If you're seeing this, you've successfully installed Tomcat. Congratulations!



Recommended Reading:
[Security Considerations HOW-TO](#)
[Manager Application HOW-TO](#)
[Clustering/Session Replication HOW-TO](#)

- [Server Status](#)
- [Manager App](#)
- [Host Manager](#)

Developer Quick Start

- [Tomcat Setup](#)
- [Realms & AAA](#)
- [Examples](#)
- [Servlet Specifications](#)
- [First Web Application](#)
- [JDBC DataSources](#)
- [Tomcat Versions](#)

Managing Tomcat

For security, access to the [manager webapp](#) is restricted. Users are defined in:

```
$CATALINA_HOME/conf/tomcat-users.xml
```

In Tomcat 9.0 access to the manager application is split between different users. [Read more...](#)

- [Release Notes](#)
- [Changelog](#)
- [Migration Guide](#)
- [Security Notices](#)

Documentation

- [Tomcat 9.0 Documentation](#)
- [Tomcat 9.0 Configuration](#)
- [Tomcat Wiki](#)

Find additional important configuration information in:

```
$CATALINA_HOME/RUNNING.txt
```

Developers may be interested in:

- [Tomcat 9.0 Bug Database](#)
- [Tomcat 9.0 JavaDocs](#)
- [Tomcat 9.0 SVN Repository](#)

Getting Help

FAQ and Mailing Lists

The following mailing lists are available:

- [tomcat-announce](#)
Important announcements, releases, security vulnerability notifications. (Low volume).
- [tomcat-users](#)
User support and discussion
- [taglibs-user](#)
User support and discussion for [Apache Taglibs](#)
- [tomcat-dev](#)
Development mailing list, including commit messages

Other Downloads

- [Tomcat Connectors](#)
- [Tomcat Native](#)
- [Taglibs](#)
- [Deployer](#)

Other Documentation

- [Tomcat Connectors](#)
- [mod_jk Documentation](#)
- [Tomcat Native](#)
- [Deployer](#)

Get Involved

- [Overview](#)
- [SVN Repositories](#)
- [Mailing Lists](#)
- [Wiki](#)

Miscellaneous

- [Contact](#)
- [Legal](#)
- [Sponsorship](#)
- [Thanks](#)

Apache Software Foundation

- [Who We Are](#)
- [Heritage](#)
- [Apache Home](#)
- [Resources](#)

Copyright ©1999-2018 Apache Software Foundation. All Rights Reserved

Tomcat web application manager dashboard allows you to deploy, undeploy, start, stop, and reload your applications. It is available at:
http://<your_domain_or_IP_address>:8080/manager/html.



Tomcat Web Application Manager

Message: OK

Manager
[List Applications](#) [HTML Manager Help](#) [Manager Help](#) [Server Status](#)

Applications					
Path	Version	Display Name	Running	Sessions	Commands
/	None specified	Welcome to Tomcat	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/docs	None specified	Tomcat Documentation	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/examples	None specified	Servlet and JSP Examples	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/host-manager	None specified	Tomcat Host Manager Application	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/manager	None specified	Tomcat Manager Application	true	2	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes

Deploy

Deploy directory or WAR file located on server

Context Path (required):


XML Configuration file URL:

WAR or Directory URL:

WAR file to deploy

Select WAR file to upload No file chosen

Tomcat virtual host manager dashboard allows you to create, delete, and manage Tomcat virtual hosts. It is available at: http://<your_domain_or_IP_address>:8080/host-manager/html.



Tomcat Virtual Host Manager

Message: OK

Host Manager			
List Virtual Hosts	HTML Host Manager Help	Host Manager Help	Server Status

Host name		
Host name	Host aliases	Commands
localhost		Host Manager installed - commands disabled

Add Virtual Host	
Host	
Name:	<input type="text"/>
Aliases:	<input type="text"/>
App base:	<input type="text"/>
AutoDeploy	<input checked="" type="checkbox"/>
DeployOnStartup	<input checked="" type="checkbox"/>
DeployXML	<input checked="" type="checkbox"/>
UnpackWARs	<input checked="" type="checkbox"/>
Manager App	<input checked="" type="checkbox"/>
CopyXML	<input type="checkbox"/>
<input type="button" value="Add"/>	

Persist configuration

Save current configuration (including virtual hosts) to server.xml and per web application context.xml files

Last update: **2020/01/23 13:32**